

Vision Blackback Stretch Elite 32



dpm
digital print media

Technical Data Sheet

Vision Blackback Stretch Elite

Knitted polyester with a black block-out rear face suitable printing UV Finished with FR treatment.

Material	100 % Polyester With additional, onesided block-out coating			
Stock widths	app. 320 cm			
Finishing	Rolled on paper cores			
Weight				
acc. to DIN EN 12127	235.00	[g/m ²]	+ - 3	[%]
Shrinkage				
Heat Shrinkage, 195 °C, 90 sec, lengthwise acc. to AA 25-02	-5.00	[%]	+ - 1	[%]
Heat Shrinkage, 195 °C, 90 sec, crosswise acc. to AA 25-02	-1.00	[%]	+ - 1	[%]
Tearing strength				
Elongation at 100 N, longitudinal direction acc. to DIN EN ISO 13934-1	18.00	[%]	+ - 10	[%]
Elongation at 100 N, cross direction acc. to DIN EN ISO 13934-1	22.00	[%]	+ - 10	[%]
Maximum tensile elongation, longitudinal direction acc. to DIN EN ISO 13934-1	50.00	[%]	+ - 20	[%]
Maximum tensile elongation, cross direction acc. to DIN EN ISO 13934-1	75.00	[%]	+ - 20	[%]
Maximum tearing strength, longitudinal direction acc. to DIN EN ISO 13934-1	min. 250.00	[N/5 cm]		
Maximum tearing strength, cross direction acc. to DIN EN ISO 13934-1	min. 620.00	[N/5 cm]		



Digital Print Media, The Heights, Ibstone Road, Stokenchurch, Bucks, HP14 3BG
T : 01494 760 240 E : sales@dpm.com W : www.dpm.com